

Sri Vijaya Visakha Milk Producers Company Limited

Akkireddy Palem, BHPV(Post), Vishakhapatnam-530012, Andhra Pradesh

GSTIN 37AAJCS7398P1Z4

TIN/CST NO: 37132885261

Phone : 0891-2517230

Excise Regn.No: AAJCS7398PEM001

Fax : 0891-2757708

CIN : U15209AP2006PTC048708

Email : purchase@visakhadairy.com

Vendor Code: V02116

PURCHASE ENQUIRY

S

ENQUIRY No: PEQE6-25-114 Date: 16-09-2025

Indent No: STRH-25-108 Indent Dt: 08-09-2025

Unit-Name : VISAKHAPATNAM

Department : PRODUCTION

Center-Name: PROD - Butter & Ghee

Bid Date 18-09-2025 upto 10 AM

File No

Ph. 0 Email ID :

Please supply the Equipment/Material Specified below. All terms and conditions incorporated here in on the reverse / attached to this purpose order including general terms and conditions of purchase.

S.No	Code	Description	Toler%	Units	Indent No:	Quantity
1	PMGHTN001	Empty Ghee Tins(15 KG Cap)		Nos	STRH-25-108 Indent:08-09-2025	5,600.00
Total (Rupees)						5,600.00

Delivery Schedule : immediately

Place of Delivery : VD-VSP

Special Note : send quotation as per enquiry


Payment Terms

Narration :

Delivery Terms :

Note : Please send your offer with GST Details

For VISAKHA DAIRY


 Head of the Department (Purchase) 16.09.25


SRI VIJAYA VISAKHA MILK PRODUCERS COMPANY LIMITED
QUALITY CONTROL DEPARTMENT- VISAKHA DAIRY, VISAKHAPATNAM - 530012


Specifications and Standards for 15 kg ghee tins

IS No.10325:2000

- | | |
|--|---|
| 1. Appearance | : 100% rust free shiny tin |
| 2. Odour | : Free from objectionable odour. |
| 3. Material thickness in mm
(Body/Top/Bottom) | : 0.28 (IS 1993) |
| 4. Internal Lacquering | : should be food grade. |
| 5. Lacquer coverage, Inner weld margin | : Resist standard Acetone/ CuSO_4 test |
| 6. Lining compound | : Food grade |
| 7. Length in mm | : 235 ± 3 |
| 8. Breadth in mm | : 235 ± 3 |
| 9. Height in mm | : 325 ± 3 |
| 10. Weight in gm | : 915 ± 15 |
| 11. Capacity | : 15 kg |
| 12. Leakage | : Zero leakage |
| 13. Mouth | : Suitable to fit closure - <i>sprout type cap</i> |
| 14. Handle wire in mm | : <u>Galvanized steel wire not less than 3.5</u> |
| 15. Handle Position | : <u>Firmly secured on top by soldering, Spot welding</u> |
| 16. Packing | : <u>6 no.s tied with nylon rope.</u> |
| 17. MSDS ,COA and FOOD GRADE | : <u>Should provide with each & every consignment.</u> |
| 18. Marking | : Each container shall bear Name , BIS NO.
Recognized trade mark, year of mfg. on the
bottom. |

Note: The product shall confirm to the IS: 10325:2000


Manager (QA)


Chief (QA)